Tender Notice

National Small Industries Corporation Limited
NSIC Bhawan Okhla
Industrial Estate New
Delhi-110020

Tel: +91-11-26826941/26826847 Email: tech@nsic.co.in

Tender no.: SIC/HO/TID/AU/12-174 Date: 2nd May, 2017

Subject: Supply, Installation & Commissioning of Wheat Flour Milling plant Capacity: 400 kg. per hour at Manica, Mozambique on Turnkey Basis.

NSIC is setting up India-Africa Incubation Centre for Small Enterprise Establishment at Manica (Mozambique).

We are pleased to invite your offer in two parts viz. (a) Technical and (b) Financial, strictly as per enclosed terms and conditions and instructions to bidders, in sealed covers for the under mentioned plant and machinery / equipment required for supply and installation at Manica (Mozambique). One set of equipment as given in "Technical Bid Schedule" of this tender document.

The detailed tender document can be obtained free of cost from Chief General Manager (TID) at the above address. The tender document can also be downloaded from NSIC website www.nsic.co.in. Any clarification on technical specifications can be obtained in writing from NSIC before tender opening. Manufacturers are welcome to have prebid meeting with NSIC for better understanding our requirements.

Please submit your lowest quotation / offer for the above requirement subject to our terms and conditions. Your offer should be submitted to Chief General Manager (TID), National Small Industries Corporation Limited, NSIC Bhawan, Okhla Industrial Estate, New Delhi-110020 latest by 18th May, 2017 till 5:30 P.M. Offers received after the last date and scheduled time shall not be considered.

The format for technical bid and financial bid shall be as per Annexure-I and Annexure-II respectively. The offer should be submitted with a covering letter as per format at Annexure-III in a sealed envelope clearly mentioning the above tender number on top of the envelope.

The technical bid shall be opened on 19th May, 2017 at 4:30 P.M. in the presence of authorized representatives of the bidders who may like to be present. The authorized representative should bring authority letter from their principals for attending the bid opening.

Note: The vendor should submit their best price while submitting their bids itself and they will not be allowed to revise the price any time thereafter.

NSIC reserves the right to reject one or all of the bids without assigning any reasons.

KINDLY READ ALL TERMS AND CONDITIONS OF "TENDER DOCUMENT" THOROUGHLY. QUOTATION NOT IN ACCORDANCE WITH THE TERMS AND CONDITIONS IS LIABLE TO BE DISQUALIFIED AND IGNORED.

Chief General Manager (TID)

Important Instructions to bidders for submission of tender

1) Preparation of Bids:

The bids should be prepared in the following manner: -

- a. The Bid shall be neatly arranged, plain and intelligible.
- b. Each page of the bid should be signed by the authorised person. Letter regarding the authorisation of such person should be obtained from the Principal / Manufacturer and enclosed with the bid.
- c. Insertions, postscripts, additions and alterations shall not be recognized, unless confirmed by bidder's signature.
- d. Bids should not contain any terms and conditions, printed or otherwise, which are not applicable to the Bid.
- e. Any conditional bid not adhering to the terms & conditions of the tender shall be rejected.
- f. The bidder should be the Principal / Original manufacturers of plant & machinery/ equipment, failing which the quotation shall not be considered.
- g. The bidders should have executed at least three purchase orders / contracts of equivalent value in the last five years. The bidder is required to submit catalogue of the plant & machinery/ equipment, complete reference of the past supply of equipment for the same or similar specification giving details of customer with name of the contact person, Fax no, phone no, E-mail.
- h. The bidders (originals manufacturers) will have to submit ink-signed offer / bid in original to NSIC. **Bids not complying with this condition shall not be considered**.
- In the Financial Bid, prices are to be indicated in both figures and words. In case of any discrepancy of value the prices quoted in words shall be considered for evaluation and establishing L1 status.
- j. No price variation clause will be entertained.

- k. Specifications are the basic essence of the "Product". Mere copying of the tender specifications by the Bidder into their bids shall not make them eligible for consideration. Appropriate and sufficient evidence of conformity by way of data (catalogues etc.) shall be furnished. There should be an item-by-item commentary on the Specifications demonstrating responsiveness of the offered equipment to the specifications.
- I. Bid with any pre-conditions (like conditional discounts) for price are liable to be "Not considered" / "Rejected".

2) Submission of Bids:

- a. Bids must be received by NSIC on or before the due date and time at the address specified in the tender document. In the event of the specified date for the submission of bids being declared a holiday for NSIC, the bid-closing deadline will stand extended to the next working day up to the same time.
- b. Any bid received by NSIC after the deadline for submission of bids, will not be accepted and returned unopened to the bidder.
- c. NSIC at its discretion may extend the deadline for the submission of bids if the bid document undergoes changes during the bidding period, in order to give prospective bidders time to take into consideration the amendments while preparing their bids.
- d. In case of receipt of inadequate numbers of bids, NSIC may extend the deadline for submission of bids giving opportunity to other bidders to participate in the bidding process to make it competitive.
- e. If the Supplier submits only one envelop / cover containing all the bids or combined bids e.g. techno-commercial bid & price bid together, the bid is liable for rejection.
- NOTE: The manufacturers should submit their best price at this stage itself and they will not be allowed to revise the price. Any revision / discount given by manufacturers subsequently will be ignored.

3) Amendment of Bidding Documents:

- a. At any time prior to the deadline for submission of bids, NSIC may, for any reason, whether on its own initiative or in response to the clarification request by a prospective bidder, modify the bid document.
- b. All prospective bidders who have requested for the bidding document will be notified of the amendment in writing, and such amendments/ modifications will be binding on them.

4) Bid opening and evaluation of Bids:

- a. The technical bids shall be opened on 19th May, 2017 at 4:30 P.M.
- b. Bidder whose technical bid is qualified based on the eligibility criteria as specified in this tender document will be considered for financial bid evaluation. The date and time of opening of the financial bid will be informed to such bidders.
- c. NSIC will open financial bids of only the technically qualified, in the presence of the bidders or their authorised representative who choose to attend the bid opening.
- d. The bidder's authorised representative who attends the bid opening shall sign an attendance register as a proof of having attended the bid opening.
- e. The bidder's name, bid prices, discounts and such other details will be announced at the time of opening of the financial bids.

5) Award of Contract

- a. The financial bids of the technically qualified bidders shall be opened by the constituted committee. Thereafter the committee shall prepare the comparative statement (CST) based on the FOR, ICD, Tughlakabad, New Delhi price quoted by the bidders. This will facilitate to shortlist the L-1 bidder quoting the lowest price.
- b. L-1 will be decided on the basis of total value of the bid.

- c. NSIC shall award the contract to the eligible bidder whose financial bid has been accepted and determined as the lowest evaluated financial bid.
- d. If more than one bidder happens to quote the same lowest price, NSIC reserves the right to award the contract to any one bidder.
- e. Separate supply order shall be placed for supply and installation of machinery and equipment required for location at Manica. The bidder shall deposit 'Security Deposit' for ₹36,000/- (Rupees Thirty Six Thousand only) for each supply orders placed for different locations.
- f. The successful bidder, on award of contract/order, must send the contract/order acceptance in writing, within 7 days of award of contract/order, failing which the EMD will be forfeited.

6) Interpretation of the clauses in the Tender Document / Contract Document

In case of any ambiguity / dispute in the interpretation of any of the clauses in this Tender Document, NSIC's interpretation of the clauses shall be final and binding on all parties.

7) <u>Earnest Money Deposit:</u>

a. The units registered with Central Purchase Organization (DGS&D), National Small Industries Corporation (NSIC) or the concerned Ministry or Department shall be exempted from the payment of Earnest Money as defined under Rule 157 of General Financial Rules (GFR), 2005.

In such case, copy of the certificate showing registration with the above mentioned institutions to be enclosed alongwith the Technical Bid.

- b. In case, the unit is not covered under a. above, it should submit the offer along with Earnest Money Deposit (EMD) for ₹36,000/- (Rupees Thirty Six Thousand only) by way of Demand Draft (DD) drawn in favour of "National Small Industries Corporation Limited" payable at New Delhi for one set of goods only (even in case the bidder is quoting for more than one set). No cash / cheque towards EMD shall be accepted. The DD for EMD should be placed inside the envelope containing technical bid. The offers without EMD shall be rejected.
- c. The EMD will be refunded to the unsuccessful bidder within 30 days from the award of contract.
- d. No interest will be allowed for earnest money deposited with the Company.
- e. The EMD shall be forfeited:
 - (i) If the bidder withdraws the bid during the period of bid validity specified in the tender.
 - (ii) If the successful bidder fails to furnish the acceptance in writing, within 7 days of award of contract/order.

8) Security Deposit

- a. The EMD of successful bidder shall be kept as 'Security Deposit' for supply of goods against each supply order and shall be released at the time of final payment after successful completion of work.
- b. In case of bidder exempted from payment of EMD (as mentioned in Para 7 a. above), 'Security Deposit' for ₹36,000/- by way of demand draft in favour of "National Small Industries Corporation Limited" payable at New Delhi should be submitted along with order acceptance against each supply order. However, the successful bidder can furnish a Bank Guarantee of Nationalized Bank of equivalent amount in lieu of 'Security Deposit' valid for one year from the date of supply order.

9) Prices:

All items are to be quoted in INR only in the format as per Annexure-II. The price quoted should be inclusive of sea worthy packing, insurance and freight on FOR, ICD, Tulglakabad (New Delhi) basis. The prices should also be inclusive of all taxes and duties as applicable. The price quoted shall be considered firm and no price escalation shall be permitted.

10) Validity of the Quote:

The validity of quote should be at least six months (180 days) from the closing date of tender. A bid valid for a shorter period shall stand rejected.

NSIC may ask for the bidder's consent to extend the period of validity. Such request and the response shall be made in writing only. A bidder agreeing to the request for extension will not be permitted to modify his bid.

11) Delivery period:

The goods shall be delivered to NSIC's C&F agent at New Delhi (or any other place as specified by NSIC) within 60 days from the date of award of contract. Part delivery shall not be permitted. Separate dispatch instruction shall be issued after inspection of goods and acceptance thereof by NSIC. No other delivery terms shall be acceptable.

12) Taxes / Duties:

- a. The bidders should be registered with sales tax / income tax department of Govt. of India and should hold a valid VAT registration certificate, as applicable.
- b. Sales tax, excise duty, VAT, octroi or any other tax shall be paid on actual as per rule applicable and on production of documentary proof. No tax concession form or proof of shipment of goods shall be issued.

13) Payment terms:

- a. 80% of order value to be released on submission of following documents:
 - i. Signed commercial Invoice-two copies certifying that the goods are exactly as per the purchase order and the specification quoted.
- ii. One copy of NSIC supply order.
- iii. Proof of delivery of the consignment to our C&F agent.
- iv. Clean report of findings issued by NSIC.
- v. Packing list two copies duly signed.
- b. Balance 20% order value shall be released after successful installation and commissioning of equipment at site and upon furnishing performance guarantee as stated at para 15 of this tender document.

14) Packing & Marking:

Consignment must be packed in Sea Worthy in strong packing cases, taking all precaution against damage during handling and sea weather corrosion.

Proper marking on the packing cases should be made for smooth handling of consignment. The supplier will be held responsible for the plant and machinery / equipment not being sufficiently and properly packed and in such eventuality the supplier shall have to transport them by rail, road at their destination, at his expense free from loss or damage.

Every package delivered under our order shall at the expense of the supplier be distinctly marked with description and quantity or contents with the consignee name and address (which shall be notified subsequently) with gross weight and net weight, with the distinctive number and mark which is also to be shown for the purpose of identification on the suppliers packing account.

Each packet shall contain a packing note quoting a number and date of our order and showing its contents in detail.

15) Performance Guarantee:

Performance Guarantee in the form of Bank Guarantee (BG) on the prescribed format @10% of order value in favour of NSIC Ltd. towards performance of the contract (Purchase Order) shall be required to be submitted by the party after successful installation of the project at site. This bank guarantee shall be valid for 18 months from date of shipment or 12 months from the date of successful completion of installation and commissioning at site whichever is later.

16) Pre-Shipment Inspection:

The plant and machinery / equipment to be supplied and packing thereof shall be subject to inspection by NSIC or third party (name shall be conveyed to the successful bidder) at manufacturer's premises prior to dispatch thereof. Approval and clean report of findings shall be submitted at the time of claiming 80% payment. Machinery & equipment including packing boxes shall be offered by the awarded unit for inspection at least 10 days before the stipulated date of delivery. Deviations, if any pointed out by the visiting inspection team, as mentioned above, shall be corrected and the machinery and equipment as per specification shall be dispatched on or before the contract delivery date.

17) Liquidated damages:

In the event of delay in supply of the goods within the stipulated period, Liquidated Damages (LD) shall be charged by NSIC @ 1½% (one-half of one percent) of the total order value per week of delay or part thereof subject to a maximum of 5% (five percent) of the order value. Supplier shall deduct the applicable LD from the first payment while raising the claim for the same.

18) Insurance:

All goods are to be insured for 110% of the FOR value of the goods by successful bidder from the works to warehouse of our C&F agent at New Delhi.

19) Installation & Commissioning:

a. The awarded bidders shall have to depute expert(s) for installation & commissioning at site as and when instructed by NSIC.

- b. No additional charges shall be payable for installation & commissioning of equipment at site except for the following:
- i. Return economy class Air Ticket shall be provided by NSIC.
- ii. Lodging shall be taken care of by NSIC.
- iii. Local conveyance shall be taken care of by NSIC.
- iv. Out of pocket allowance as per MEA rate shall be paid by NSIC.
- v. Skilled and unskilled workers shall be provided by Host country at site.
- vi. The supplier has to inform in advance about the material handling facilities to be arranged by host country for successful installation, commissioning, training and pilot production from the machines and equipment supplied.
- c. Time and manpower required (skilled/unskilled) for erection & commissioning should be clearly given in terms of working days and number respectively.
- d. The supplier will be required to train for at least 7 days the operators as decided by NSIC / host country.

20) After Sales Service / Warranties by Suppliers:

The equipment shall be warranted for any manufacturing defect for a period of 18 months from the date of shipment or 12 months from the date of successful completion of installation and commissioning at site, whichever is later.

Should any part or parts fail or proved defective within the period specified above, owing to defect in design, material or workmanship, the supplier will have to replace them at the place of installation free of all charges.

During the warranty period, expert(s) shall be deputed at site by the awarded unit whenever found essential and which cannot be undertaken locally or by the NSIC's experts including rectifying any defect / malfunctioning of plant & machinery. The cost of deputation of expert(s) and any other associated expenditure shall be borne by the awarded unit.

21) <u>Technical Documents:</u>

The awarded unit shall provide technical documents like operation and maintenance manual etc. in English language in three copies for each items of equipment. Two copies to go with the consignment, one copy to be forwarded to NSIC

office.

22) Risk Purchase:

In case of delays in supplies / defective supplies or non-fulfillment of any other terms and conditions given in the Supply Order, NSIC may cancel the supply order in full or part thereof, and may also make the purchase of such material from elsewhere / alternative source at the risk and cost of the supplier.

In case vendor does not agree to above risk purchase clause, their offer is liable to be rejected. In case any vendor accepts risk purchase clause initially and subsequently declines to honour the term in the eventuality of RISK PURCHASE, they may be banned for business with NSIC.

23) Cancellation of Bids

- a. NSIC reserves the rights to cancel any bid without assigning any reasons.
- b. NSIC reserves the rights to cancel bids and re-float a fresh tender, at any time after opening of the bids, in case it finds the response to its bid are not meeting its requirement. This shall be at the sole discretion of NSIC.

24) Blacklisting / Debarring of Firm

- a. Units blacklisted by any Government Departments / PSUs are not eligible to participate in the tender.
- b. If the unit(s) commits breach of contract, it shall be black listed / debarred for further business with NSIC for a declared period.

25) Post Tender Negotiations

- a. NSIC reserves the right to conduct negotiations on the `Price' and 'other commercial terms' with the lowest ranked offerer, and
- b. If so required by NSIC, supplier may have to share their cost data / costing sheet with NSIC.

26) Force Majeure

If at any time during the currency of this contract, the performance in whole or in part, by either party of any obligations under this contract shall be prevented or delayed by reason, of any war, hostilities, acts of the public enemy, civil commotion, sabotage, fires, explosions, epidemics, quarantine, restrictions or acts of GOD (hereinafter referred to as events), then provided notice of happening of any such events is given by either party to other within ten days from the date of occurrence thereof, neither party shall reason of such events be entitled to terminate this contract nor shall either party have any such non-performance and delay is resumed as soon as practicable after such events has come to an end or ceased to exist. If the performance in whole or part of any obligation under this contract is prevented or delayed by reason or any such event claims for extension of time shall be granted for period considered reasonable by the purchaser subject to prompt notification by the seller to the purchaser of the particulars of the events and supply to the purchaser if required of any supporting evidence. Any waiver of time in respect of partial installment shall not be deemed to be a waiver of time in respect of remaining deliveries.

Annexure-I

Format for technical bid

One set of Wheat Flour Milling plant Capacity: 1000 kg. per hour for Supply, Installation & Commissioning at Manica (Mozambique). One set of equipment consisting of the following: 1. Cleaning Section consisting of: 1. Intake hopper with stand to feed the material: Hopper stand to be of S.S, structure and plate of 3mm thickness. Hopper to be provided with magnetic grill and feed control slide gate. All items to be buff finished. 2. Bucket elevator (to convey the material vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp. x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from 145WG sheet - should be highly efficient and	SI.	Tender requirements	Quantity	Compliance					
Supply, Installation & Commissioning at Manica (Mozambique). One set of equipment consisting of the following: 1. Cleaning Section consisting of: 1. Intake hopper with stand to feed the material: Hopper stand to be of S.S, structure and plate of 3mm thickness. Hopper to be provided with magnetic grill and feed control slide gate. All items to be buff finished. 2. Bucket elevator (to convey the material vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300°x 150°width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sleves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sleving tray from SS304 Sheet having double deck sleving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from	No.			(Yes/No)					
1. Cleaning Section consisting of: 1. Intake hopper with stand to feed the material: Hopper stand to be of S.S., structure and plate of 3mm thickness. Hopper to be provided with magnetic grill and feed control slide gate. All items to be buff finished. 2. Bucket elevator (to convey the material vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sleves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sleving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
1. Cleaning Section consisting of: 1. Intake hopper with stand to feed the material: Hopper stand to be of S.S., structure and plate of 3mm thickness. Hopper to be provided with magnetic grill and feed control slide gate. All items to be buff finished. 2. Bucket elevator (to convey the material vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from	1 11 3								
 Intake hopper with stand to feed the material: Hopper stand to be of S.S, structure and plate of 3mm thickness. Hopper to be provided with magnetic grill and feed control slide gate. All items to be buff finished. Bucket elevator (to convey the material vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from 	One set of equipment consisting of the following:								
 Intake hopper with stand to feed the material: Hopper stand to be of S.S, structure and plate of 3mm thickness. Hopper to be provided with magnetic grill and feed control slide gate. All items to be buff finished. Bucket elevator (to convey the material vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from 	1	1 Cleaning Section consisting of: One Set							
Hopper stand to be of S.S., structure and plate of 3mm thickness. Hopper to be provided with magnetic grill and feed control slide gate. All items to be buff finished. 2. Bucket elevator (to convey the material vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
magnetic grill and feed control slide gate. All items to be buff finished. 2. Bucket elevator (to convey the material vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		• •							
items to be buff finished. 2. Bucket elevator (to convey the material vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		3mm thickness. Hopper to be provided with							
 Bucket elevator (to convey the material vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from 									
vertically) – 3 Nos. suitable for 100mm bucket, complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
complete with belt buckets, bolts, electric gear motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		·							
motor, coupling, etc: Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		9.							
Head and Boot of the elevator to be fabricated from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
from 12SWG S.S and have dia300"x 150"width crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		·							
crown face cast iron pulleys fitted with SS shaft mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
mounted on UCP/UCT-206 and boxes to be fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
fabricated from 16SWG SS304 sheet. Full Buff finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		, ,							
finish. With 0.5HPx 72rpm geared motor, L-110 coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
coupling - Machine should have Noiseless operation, should provide back flush arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
arrangement of belt. Inspection glass to inspect inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
inside movement during operation of machine 3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		operation, should provide back flush							
3. Classifier Separator (to remove all large and small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
small size impurities from the grain) 1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		- · · · · · · · · · · · · · · · · · · ·							
1000x1500mm fitted with 0.5hp.x 2Nos. Vibro electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		- · · · · · · · · · · · · · · · · · · ·							
electric motor complete with aspiration channel and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		•							
and perforated sieves frame. The base frame of the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
the machine to be fabricated from Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		·							
having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from									
with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		having double deck sieving frame inside fitted							
frame. Full Buff finish. 4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		with perforated sheets. The sieving tray							
4. Dust Cyclone (to collect dusty particles from the aspirated air) – dia 960mm to be made from		mounted on vibrating pad fitted with base							
the aspirated air) – dia 960mm to be made from									
14SWG sheet- should be highly efficient and		·							
easy to maintain.		3							
5. Airlock (to discharge dusty particles from the									
cyclone): Main casing to be of cast iron having a cast iron rotor inside fitted with En-8 shaft									
mounted on ball bearings at both ends. High									
Efficiency, Easy to maintain, powered with 1HP		S S							
x 56rpm geared motor		· · · · · · · · · · · · · · · · · · ·							

6. Low Pressure Fan (to provide air resistance to the machines for dust control in the plant): Main casing to be M. S. sheet, plate, angle, etc. having a fully dynamic balanced rotor inside mounted directly on motor shaft with 5HP x 1440rpm. Electric motor. 7. **De-stoner** (to remove stones from the grain) fitted with 2hp. electric motor. Base frame of Structure steel covered with SS304 Sheet of 16SWG having sieving frame inside fitted with perforated sheets (made of SS304) mounted on 4 spring steel flat, full buff finish. Machine shall be capable to remove skins, particles, roots, fibers, etc. from Wheat kernel. Should come with control panel. Noiseless and easy operation. Inspection glass to inspect inside movement during operation of machine. 8. Screw Conveyor (for horizontal conveying of material) dia 150mm: Should be completely made of SS304, buff finish. Main casing of 14SWG and blade of 3mm sheet fitted with dia 32x38mm. 'B' class Pipe having worm hangers at suitable distance mounted on shafts at both ends with bearings UCF-206 & coupling L - 110. Noiseless operation and easy to maintain. All the electricals should be given complete with electrical motors (reputed international make), electrical starter, switch, overload protector, wiring, etc. Any other provision required for smooth running of the machines should be included. 2. Milling Section consisting of: One Set 1. Milling Machines (to grind the material) - 2 Nos. dia 30" with grinding stones (Choyal Brand). The base frame from M.S. angle of 90x90x8mm with floor plate of SS304-10mm thickness fitted with heavy duty shaft of SS304 mounted on 3Nos. ball bearings and 1No. Thrust bearings Machine should have feed control and pressure control system to control the granularity of flour. Noiseless operation and Easy to maintain, powered with 20HP x 960rpm. All contact parts except Grinding Stones to be made of SS304. 2. **Pneumatic lifts** (to shift flour from Milling to Centrifugal M/c. for Sieving). All material contact parts except Airlock to be of SS304, with accessories including: i) ERW lift pipe dia 113mm 20ft. ii) Long radios bend dia 113mm. 1No. iii) Pneumatic Cyclone dia363mm. 1 No. iv) Pneumatic Feeder dia113mm. 1 No.

v) Inspection glass with rubber 1 set

	viii) Pipe clamp dia113mm 3 Nos.		
	3. Centrifugal Machine (to separate bran from		
	flour) complete with SS304 sieves (jaali),		
	pulleys & belt etc. Main base frame of machine		
	is fabricated from SS202 channel of 3"x1.5"		
	covered with SS304 Sheet of 18Swg. Machine		
	should consist of SS304 - double rotating drums		
	inside fitted with SS304 shaft (dia50mm)		
	mounted on plumber block and bearing at both		
	ends. Machine should be provided with self-		
	cleaning brush for sieves. Should run with min.		
	3HP x960rpm motor, have noiseless operation		
	and easy to maintain. All material contact parts		
	except bolting cloth to be made of SS304.		
	4. High Pressure Fan (to provide air resistance		
	to the pneumatic lift to convey the material)		
	suitable with 3HP x 2880 rpm motor: Main		
	casing of M.S sheet plate, angle, etc. having		
	fully Accurate & Dynamic balanced rotor inside,		
	mounted directly on motor shaft. High Efficiency		
	and easy to maintain.		
	All the electricals should be given complete		
	with electrical motors (reputed international		
	make), electrical starter, switch, overload		
	protector, wiring, etc. Any other provision		
	required for smooth running of the machines		
	should be included.		
3.	should be included. Open Type Dust Collector with sleeves (filtering	One Set	
3.	should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos.	One Set	
3.	should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304	One Set	
3.	should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg	One Set	
3.	should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304	One Set	
3.	should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg	One Set	
3.	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and	One Set One set	
	should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods.		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following:		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set c. Hammers 200gr., 500gr., 1Kg 1 Each		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set c. Hammers 200gr., 500gr., 1Kg 1 Each d. Screw driver 8", 12" - 1 Each		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set c. Hammers 200gr., 500gr., 1Kg 1 Each d. Screw driver 8", 12"- 1 Each e. Hand grinder AG-4 -1No.		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set c. Hammers 200gr., 500gr., 1Kg 1 Each d. Screw driver 8", 12" - 1 Each e. Hand grinder AG-4 -1No. f. Drill Machine with stand 34" cap1 No.		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set c. Hammers 200gr., 500gr., 1Kg 1 Each d. Screw driver 8", 12" - 1 Each e. Hand grinder AG-4 -1No. f. Drill Machine with stand 3/4" cap1 No. g. Slid wrench 12' -1 No.		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set c. Hammers 200gr., 500gr., 1Kg 1 Each d. Screw driver 8", 12" - 1 Each e. Hand grinder AG-4 -1No. f. Drill Machine with stand 34" cap1 No.		
	should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set c. Hammers 200gr., 500gr., 1Kg 1 Each d. Screw driver 8", 12" - 1 Each e. Hand grinder AG-4 -1No. f. Drill Machine with stand ¾" cap1 No. g. Slid wrench 12' -1 No. h. Welding set -1 No.		
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set c. Hammers 200gr., 500gr., 1Kg 1 Each d. Screw driver 8", 12" - 1 Each e. Hand grinder AG-4 -1No. f. Drill Machine with stand ¾" cap1 No. g. Slid wrench 12' -1 No. h. Welding set -1 No. (please specify each item with detailed		
4.	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set c. Hammers 200gr., 500gr., 1Kg 1 Each d. Screw driver 8", 12" - 1 Each e. Hand grinder AG-4 -1No. f. Drill Machine with stand ¾" cap1 No. g. Slid wrench 12' -1 No. h. Welding set -1 No. (please specify each item with detailed specifications / quantity - use separate sheet)	One set	
	Should be included. Open Type Dust Collector with sleeves (filtering cloth) – 6 Nos. Storage tanks with Lid, (2 Nos.) made from SS 304 with thickness of sheet 18 SWG. Capacity: 1000 Kg Aspiration trunk line, gravity pipes & structure and other material required + Hardware goods. Complete set of tools, jigs & fixtures required for installations (Anti-vibration mountings/ foundation bolts, etc.), tools for smooth operations & maintenance of machines (hand tools, special tools including electrical circuit diagrams and electrical spares, etc.) including the following: a. Spanner set 6-32mm-1Set b. Ring Spanner set 6-32mm-1 Set c. Hammers 200gr., 500gr., 1Kg 1 Each d. Screw driver 8", 12" - 1 Each e. Hand grinder AG-4 -1No. f. Drill Machine with stand ¾" cap1 No. g. Slid wrench 12' -1 No. h. Welding set -1 No. (please specify each item with detailed		

Signature of Bidder
Seal of Bidder

SIC/HO/TID/AU/12-174

Electrical Spares

- a. Relay of various sizes- 5 pcs each as per panel requirement
- b. Contactors of various sizes -2 pcs each as per panel requirement
- c. Fuse of various sizes- 2 Lots
- d. Indicators bulbs- 2 sets
- e. Amp. & Voltage meters- 1Pcs. each

Other Spares:

- a. 100mm. Buckets- 5dozens
- b. Bucket bolts- 2 packets
- c. Belt fastening bolt- 1dozen
- d. UCP 206- 6 Nos.
- e. UCF 206- 6 Nos.
- f. UCT 206- 6 Nos.
- g. Vibration pad for separator- 2 Set
- h. Inlet sieve for separator- 8 Nos.
- i. Worm hanger with fiber bush- 2 Set
- j. Complete set of bearing for Mills (chakkies)- 1 Set
- k. Complete set of bearing for Centrifugal- 1 Set
- Complete set of V-belts for Mills (chakkies)- 2 Set
- m. Complete set of V-belts for Centrifugal 1 Set
- n. Bolting clothes- 1 Set
- o. Grinding Stone for Mill(chakkie) 2 pairs
- p. Couplings L 110 1 dozen
- q. Chain required for centrifugal with lock- 1No.
- r. Grinding Wheal 4"- 100pcs.
- s. Drill 3/4" 2 pcs.
- t. Chain block 1ton with chain 20' 1 No.

(please specify each item with detailed specifications / quantity - use separate sheet)

Note:

The aspects mentioned below must be noted while submitting bids for the above mentioned plant and machinery / equipment:

- a) Finished products should have quality similar to norms of Bureau of Indian Standards / FPO AGMARK, wherever applicable.
- b) All machines / equipment should be compatible with 220 V Single Phase, 380-400 V Three Phase 50 cycle per second supply. Electrical wiring for interconnection of the machines upto main supply wherever necessary should be supplied along with machines.
- c) In case foundation of the machine is required for installation, necessary foundation bolts, pads, washers etc. should be supplied along with foundation drawing.

Signature of Bidder
Seal of Bidder

- d) All machines should be supplied with electricals, raw material handling and finished material packing arrangement along with working tools.
- e) List out the technical specification, additional equipment required, if any, for smooth running of the project.
- f) All machines should be complete and ready for production of stated capacity and should be supplied with operation and maintenance manual.

Enclosures:

- 1. Company profile with catalogues.
- 2. Detailed specification of all items mentioned above.
- 3. Copy of client list / purchase orders/ contracts of similar nature and size in the last five years.
- 4. Copy of Pan Card / Sales tax / VAT registration certificate.
- 5. Copy of Udyog Aadhaar SSI / MSME Memorandum part—II / NSIC registration certificate, if applicable.
- 6. Demand draft for ₹36,000/- as EMD.

Financial price schedule

Annexure-II

SI.	Description and Technical	Ougntity	Drice	Tax &	Total
	Description and Technical	Quantity	Price		Total
No.	specification		(INR)	Duties	price
				(As	(FOR,
				applicable	Delhi)
)	(INR)
				(INR)	
One	set of Wheat Flour Milling plant Ca	apacity: 40	00 kg. per	hour at consi	sting of the
	wing:	T -	T		
1.	Cleaning Section consisting of:	One Set			
	9. Intake hopper with stand to				
	feed the material: Hopper stand				
	to be of S.S, structure and plate				
	of 3mm thickness. Hopper to be				
	provided with magnetic grill and				
	feed control slide gate. All items				
	to be buff finished.				
	10. Bucket elevator (to convey the				
	material vertically) – 3 Nos.				
	suitable for 100mm bucket,				
	complete with belt buckets,				
	bolts, electric gear motor,				
	coupling, etc:				
	Head and Boot of the elevator to				
	be fabricated from 12SWG S.S				
	and have dia300"x 150"width				
	crown face cast iron pulleys				
	fitted with SS shaft mounted on				
	UCP/UCT-206 and boxes to be				
	fabricated from 16SWG SS304				
	sheet. Full Buff finish. With				
	0.5HPx 72rpm geared motor, L-				
	110 coupling - Machine should				
	have Noiseless operation,				
	should provide back flush				
	arrangement of belt. Inspection				
	glass to inspect inside				
	movement during operation of				
	machine				
	11.Classifier Separator (to				
	remove all large and small size				
	impurities from the grain)				
	1000x1500mm fitted with				
	0.5hp.x 2Nos. Vibro electric				
	motor complete with aspiration				
	channel and perforated sieves				
	frame. The base frame of the				
	machine to be fabricated from				

Signature of Bidder
Seal of Bidder

SIC/HO/TID/AU/12-174

- Structure steel SS202 and sieving tray from SS304 Sheet having double deck sieving frame inside fitted with perforated sheets. The sieving tray mounted on vibrating pad fitted with base frame. Full Buff finish.
- 12. Dust Cyclone (to collect dusty particles from the aspirated air)
 dia 960mm to be made from 14SWG sheet- should be highly efficient and easy to maintain.
- 13. Airlock (to discharge dusty particles from the cyclone):
 Main casing to be of cast iron having a cast iron rotor inside fitted with En-8 shaft mounted on ball bearings at both ends. High Efficiency, Easy to maintain, powered with 1HP x 56rpm geared motor
- 14. Low Pressure Fan (to provide air resistance to the machines for dust control in the plant): Main casing to be M. S. sheet, plate, angle, etc. having a fully dynamic balanced rotor inside mounted directly on motor shaft with 5HP x 1440rpm. Electric motor.
- 15. **De-stoner** (to remove stones from the grain) fitted with 2hp. electric motor. Base frame of Structure steel covered with SS304 Sheet of 16SWG having sieving frame inside fitted with perforated sheets(made SS304) mounted on 4 spring full buff finish. steel flat, Machine shall be capable to remove skins, particles, roots, fibers, etc. from Wheat kernel. Should come with control panel. Noiseless and easy operation. Inspection glass inspect to inside movement during operation of machine.
- 16.**Screw Conveyor** (for horizontal conveying of material) dia 150mm: Should be completely made of SS304, buff finish. Main casing of 14SWG and blade of 3mm sheet fitted

Signature of Bidder Seal of Bidder

SIC/HO/TID/AU/12-174 with dia 32x38mm. 'B' class Pipe having worm hangers at suitable distance mounted on shafts at both ends with bearings UCF-206 & coupling L - 110. Noiseless operation and easy to maintain. All the electricals should be given complete with electrical motors (reputed international make), electrical starter. switch, overload protector, wiring, etc. Any other provision required for smooth running of machines should included. Milling Section consisting of: One Set 2. 5. Milling Machines (to grind the material) - 2 Nos. dia 30" with grinding stones (Choyal Brand). The base frame from M.S. angle of 90x90x8mm with floor plate of SS304-10mm thickness fitted with heavy duty shaft of SS304 mounted on 3Nos. ball bearings 1No. Thrust bearings and Machine should have feed control and pressure control system to control the granularity of flour. Noiseless operation and Easy to maintain, powered with 20HP x 960rpm. All contact parts except Grinding Stones to be made of SS304. 6. Pneumatic lifts (to shift flour from Milling to Centrifugal M/c. for Sieving). All material contact parts except Airlock to be of SS304, with accessories including: ix) ERW lift pipe dia 113mm 20ft. x) Long radios bend dia 113mm. 1No. xi) Pneumatic Cyclone dia363mm. 1 No. xii) Pneumatic Feeder dia113mm. 1 No. Inspection glass with xiii) rubber 1 set

Air

xv) Rubber dia 113mm. 3 Nos.

stand 1 set

xiv)

lock with glass

mountings/

One set

required + Hardware goods.

(Anti-vibration

Complete set of tools, jigs &

fixtures required for installations

	SIC/HO/TID/AU/12-174
foundation bolts, etc.), tools for	
smooth operations & maintenance	
of machines (hand tools, special	
tools including electrical circuit	
diagrams and electrical spares,	
etc.) including the following:	
a. Spanner set 6-32mm-1Set	
b. Ring Spanner set 6-32mm-1 Set	
c. Hammers 200gr., 500gr., 1Kg	
1 Each	
d. Screw driver 8", 12"- 1 Each	
e. Hand grinder AG-4 -1No.	
f. Drill Machine with stand 3/4" cap.	
-1 No.	
g. Slid wrench 12' -1 No.	
h. Welding set -1 No.	
Total price FOR, ICD, Tuglakabad,	
New Delhi (Sl. No. 1 to 4)	

Lump sum price for one set of machinery & equipment (FOR, ICD,	
Tuglakabad, New Delhi : ₹	
(in words Rupees)

Spares & Raw Materials

SI.	Description and Technical specification	Qty.	Price	Tax &	Total price
No			(INR)	Duties	(FOR,
				(INR)	Delhi)
1.	 Electrical Spares a. Relay of various sizes- 5 pcs each as per panel requirement b. Contactors of various sizes -2 pcs each as per panel requirement c. Fuse of various sizes- 2 Lots d. Indicators bulbs- 2 sets 	set			
	e. Amp. & Voltage meters- 1Pcs. each Other Spares: a. 100mm. Buckets- 5dozens b. Bucket bolts- 2 packets c. Belt fastening bolt- 1dozen d. UCP - 206- 6 Nos. e. UCF - 206- 6 Nos. f. UCT - 206- 6 Nos. g. Vibration pad for separator- 2 Set h. Inlet sieve for separator- 8 Nos. i. Worm hanger with fiber bush- 2 Set j. Complete set of bearing for Mills (chakkies)- 1 Set				

Signature of Bidder Seal of Bidder

SIC/HO/TID/AU/12-174

k. Complete set of bearing for Centrifugal- 1		
Set		
I. Complete set of V-belts for Mills (chakkies)-		
2 Set		
m. Complete set of V-belts for Centrifugal - 1		
Set		
n. Bolting clothes- 1 Set		
o. Grinding Stone for Mill(chakkie) - 2 pairs		
p. Couplings L - 110 - 1 dozen		
q. Chain required for centrifugal with lock-		
1No.		
r. Grinding Wheal 4"- 100pcs.		
s. Drill ³ / ₄ " - 2 pcs.		
t. Chain block 1ton with chain 20' - 1 No.		

Note: The above price should be inclusive of sea-worthy packing, transportation and insurance and Taxes & Duties etc.

Annexure-III

Format of covering letter

Ref. No.: Date:
Chief General Manager (TID) National Small Industries Corporation Limited NSIC Bhawan, Okhla Industrial Estate, New Delhi-110020.
Ref.: Tender No SIC/HO/TID/AU/12-174 dated 2 nd May, 2017 for one set of Wheat Flour Milling plant Capacity: 1000 kg. per hour at for Supply, Installation & Commissioning at Manica, Mozambique.
Dear Sir,
With reference to above tender notice, we are submitting herewith our offer for above as per following documents:
 Technical bid in prescribed format as Annexure-I in sealed envelope no.1 along with enclosures (No financial figures should be mentioned directly or indirectly in technical bid).
 EMD for ₹36,000/- in the form of Demand Draft in favour of "National Small Industries Corporation Limited" payable at New Delhi along with technical bid in an envelope marked "EMD" placed inside sealed envelope no.1.
3. Financial bid in prescribed format in sealed envelope no.2.
We hereby agree to fully abide by all the terms & condition of this tender.
Thanking you,
Yours faithfully,
Name Designation

Annexure-IV

Proforma for Bank Guarantee

In consideration of the National Small Industries Corporation Ltd. (NSIC), Okhla Industrial Estate, New Delhi (hereinafter called the Company') having agreed to exempt
Contractor' which term includes Suppliers for the purpose of this Bond) from the demand under the terms and conditions of an Agreement date.
called the said 'Agreement') of Security Deposit for the due fulfillment by the said Contractor of the terms and conditions contained in the said Agreement, on production of a Bank Guarantee for ₹only).
a. We,(Indicate the name of the Bank) (hereinafter referred to as the 'Bank') at the
request(Contractor(s) do hereby undertake to pay to the Company an amount not exceeding ₹ against any loss or damage
caused to or suffered or would be caused to or suffered by the Company by reason of any breach by the said Contractor (s) of any of the terms and conditions contained in the said Agreement.
b. We,(indicate the name of the Bank) do hereby undertake to pay
the amounts due and payable under this guarantee without any demur, merely on a demand from the Company stating that the amount claimed is due by way of loss or damage caused to or would be caused to or suffered by the Company by reason of breach by the said Contractor(s), of any of the terms of conditions contained in the said Agreement or by reason of the contractor(s), failure to perform the said Agreement. Any such demand made on the Bank shall be conclusive as regards the amount due and payable by the Bank under this guarantee. However, our liability under this guarantee shall be restricted to an amount not exceeding the same of the contractor of
c. We undertake to pay to the Company any money so

c. We undertake to pay to the Company any money so demanded notwithstanding any dispute or disputes raised by the Contractor(s) in any suit or proceeding pending before any court or Tribunal relating thereto our liability under this present being absolute and unequivocal.

of our liability have no claim					ctor(s)	shall
d. We, Bank)						the the
Guarantee her the period the Agreement ardues of the Cobeen fully pa (NSIC) certification and according claim under the liability under the control of the c	nat would be not that it stompany und its continuous mand its continuous mand property and property dischargenis guarantee	e taken for hall continue er or by virtulational Smalerms and concerty carried ed this guate is made on	the perfue to be educe of the led or distributed the led or distribu	formance inforceable said Agree charged or the said colonial and t	of the e till all ement or till oration Agreem of tracto deman before	said I the have Ltd. nent r(s) d or the
e. We, Bank)						the the
Company that the Company shall have the fullest liberty without our consent and without affecting in any manner our obligations hereunder to vary any of the terms and conditions of the said Agreement or to extend time of performance by the said contractor(s) form time to time or to postpone for any time or from time to time any of the power exercisable by the company against the said contractor(s) and to forbear or enforce any of the terms and conditions relating to the said Agreement and we shall not be relieved from our liability by any reason of any such variation or extension being granted to the said contractor(s) or for any forbearance, act or omission on the part of the company or any indulgence by the company to the said contractor(s) or by any such matter or thing whatsoever which under the law relating to sureties would but for this provision have effect of so relieving us.						
f. This guardent constitution of			_	to the ch	ange ir	า the
g. We, bank)		_(indicate I	the astly und	name ertake not	of to rev	the oke
this guarantee of the Compar Dated the For	ny in writing.	_		•		ent

The payment so made by us under this bond shall be a valid discharge